

Section 1: IDENTIFICATION		
Product Name:	Landscape Oil	
Synonyms:	Mineral Oil 99%.	
Product Use:	Spray Emulsifiable Insecticide. PCP Registration No. 28124	
Restrictions on Use:	Not available.	
Manufacturer/Supplier:	Plant Products Inc. 50 Hazelton Street Leamington, Ontario N8H 1B8	
Phone Number:	519-326-9037 Toll free number 1-800-387-2449 (English) Toll free number 1-800-361-9184 (French)	
Emergency Phone:	CANUTEC: 1-888-CAN-UTEC (226-8832), 613-996-6666 or *666 or a cellular phone	
Date of Preparation of SDS:	June 14, 2021	
Section 2: HAZARD(S) IDENTIFICATION		

GHS INFORMATION

Classification: Aspiration Hazard, Category 1

LABEL ELEMENTS

Hazard Pictogram(s):



Signal Word: Danger

Hazard May be fatal if swallowed and enters airways. Statements:

Precautionary Statements

Prevention: Not applicable.

- **Response:** IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
 - Storage: Store locked up.
- **Disposal:** Dispose of contents and container in accordance with applicable regional, national and local laws and regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients with Unknown Toxicity: None.

This material is considered hazardous by the Hazardous Products Regulations.



Date of Preparation: June 14, 2021

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS				
Ingredient(s)		Common name /	CAS No.	% wt./wt.
Distillates (petroleum), solvent-dewaxed light paraffinic		Synonyms Not available.	64742-56-9	98 - 100
Poly(oxy-1,2-ethane dodecylomegahy	• • •	Dodecyl alcohol, ethoxylated	9002-92-0	0 - 2
	Section 4:	FIRST-AID MEASURES		
Inhalation:	If inhaled: Call a point	son center or doctor if y	/ou feel unwell.	
Acute and delayed symptoms and effects: Vapours and/or mists which may be formed at elevated temperatures may be irritating. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.				
Eye Contact:	If in eyes: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center or doctor if you feel unwell. For contact with heated product, flush immediately with plenty of cool water for at least 15 minutes. Immediately call a poison center or doctor.			
	Acute and delayed symptoms and effects: Slightly irritating to the eyes. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Hot liquid product may cause serious thermal burns on direct contact.			
Skin Contact:	If on skin: Wash with plenty of water. Call a poison center or doctor if you feel unwell. For contact with heated product, flush immediately with plenty of cool water for at least 15 minutes. Immediately call a poison center or doctor.			
	cause skin dryness	ymptoms and effects: M and defatting of the skin welling, and itching. Ho as on direct contact.	n. Signs/symptoms	may include
Ingestion:	poison center or doo	mouth. Do NOT induce ctor. If vomiting occurs e risk of aspiration. Ne son.	naturally, have victi	im lean
	enters airways. May	ymptoms and effects: N cause gastrointestinal ain, stomach upset, na	irritation. Signs/syr	mptoms may
General Advice:		or if you feel unwell, see DS where possible).	ek medical advice i	mmediately
Note to Physicians:	Symptoms may not	appear immediately.		



Section 5: FIRE-FIGHTING MEASURES

FLAMMABILITY AND EXPLOSION INFORMATION

Not flammable or combustible by WHMIS criteria. Product will burn if involved in a fire.

Sensitivity to Mechanical Impact: Sensitivity to Static Discharge:	This material is not sensitive to mechanical impact. This material is sensitive to static discharge at temperatures at or above the flash point.
MEANS OF EXTINCTION	
Suitable Extinguishing Media:	Small Fire: Dry chemical, CO2, water spray or regular foam.
	Large Fire: Water spray, fog or regular foam. Move containers from fire area if you can do it without risk.
Unsuitable Extinguishing Media:	Do not spray water onto burning product as this may cause spattering and spreading of the flame.
Products of Combustion:	Oxides of carbon.
Protection of Firefighters:	Fire may produce irritating, corrosive and/or toxic gases. Runoff from fire control or dilution water may cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Section 6: ACCIDENTAL RELEASE MEASURES		
Emergency Procedures:	Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).	
Personal Precautions:	Do not touch or walk through spilled material. Use personal protection recommended in Section 8.	
Environmental Precautions:	Keep out of drains, sewers, ditches, and waterways.	
Methods for Containment:	Stop leak if without risk. Do not flush to sewer or allow to enter waterways.	
Methods for Clean-Up:	Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.	
Other Information:	See Section 13 for disposal considerations.	
Section 7: HANDLING AND STORAGE		

Handling:

Do not swallow. Do not breathe mist, vapours, or spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Grounding of containers/pouring equipment is necessary when transferring hot liquid product. Follow all SDS/label precautions even after container is emptied because it may contain product residue. See Section 8 for information on Personal Protective Equipment.



SAFETY DATA SHEET

Storage:

Protect from sunlight. Store in a cool, well-ventilated place. Keep container tightly closed. Store locked up. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines Component

Distillates (petroleum), solvent-dewaxed light paraffinic [CAS No. 64742-56-9]

ACGIH: 5 mg/m³ (TWA); A4 (2009); For Mineral oil, excluding metal working fluids; Pure, highly and severely refined

OSHA: 5 mg/m³ (TWA); For Oil mist, mineral.

Dodecyl alcohol, ethoxylated [CAS No. 9002-92-0]

ACGIH: No TLV established. **OSHA:** No PEL established.

PEL: Permissible Exposure Limit **TLV:** Threshold Limit Value **TWA:** Time-Weighted Average

Engineering Controls:

Not normally required.

PERSONAL PROTECTIVE EQUIPMENT (PPE)



Eye/Face Protection:

Hand Protection:

Skin and Body Protection:

Respiratory Protection:

Wear chemical safety goggles. Use equipment for eye protection that meets the standards referenced by CSA Standard CAN/CSA-Z94.3 for Personal Protective Equipment.

Wear protective gloves. Neoprene, nitrile or Viton® gloves are recommended. If product is hot, thermally protective gloves are recommended. Consult manufacturer specifications for further information.

Wear protective clothing. Clothing with full length sleeves and pants should be worn.

If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4, with organic vapor cartridge, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the airpurifying respirators.



Date of Preparation: June 14, 2021

General Hygiene Considerations:

Handle according to established industrial hygiene and safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to ensure adequate protection.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES		
Appearance:	Clear liquid.	
Colour:	Colourless.	
Odour:	Slight.	
Odour Threshold:	Not available.	
Physical State:	Liquid.	
pH:	Not available.	
Melting Point / Freezing Point:	-15 °C (5 °F) (Pour Point)	
Initial Boiling Point:	264 °C (507.2 °F) (ASTM D2887)	
Boiling Range:	264 to 436 °C (507.2 to 816.8 °F) (ASTM D2887)	
Flash Point:	172 °C (341.6 °F) (ASTM D92)	
Evaporation Rate:	Not available.	
Flammability (solid, gas):	Not applicable.	
Lower Flammability Limit:	Not available.	
Upper Flammability Limit:	Not available.	
Vapor Pressure:	0.00011 kPa (0.0008 mmHg) at 20 °C(68 °F)	
Vapor Density:	Not available.	
Relative Density:	0.85 (Water = 1) at 16 °C (60.8 °F) (ASTM D1298)	
Solubilities:	Miscible in water.	
Partition Coefficient: n- Octanol/Water:	2 to ≥ 6	
Auto-ignition Temperature:	343 °C (649.4 °F) (ASTM D2155)	
Decomposition Temperature:	Not available.	
Viscosity:	12 cSt at 40 °C(104 °F) 69 SUS at 37.8 °C(100 °F)	
Percent Volatile, wt. %:	Not available.	
VOC content, wt. %:	Not available.	
Density:	0.85 g/cm³ at 15 °C (59 °F) (ASTM D1250)	
Coefficient of Water/Oil Distribution:	Not available.	

Date of Preparation: June 14, 2021

Reactivity: Contact with incompatible materials. Sources of ignition. Exposure to heat. **Chemical Stability:** Stable under normal storage conditions. **Possibility of Hazardous** Under normal conditions of storage and use, hazardous reactions Reactions: will not occur. Conditions to Avoid: Contact with incompatible materials. Sources of ignition. Exposure to heat. Incompatible Materials: Oxidizers. Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition products may include the following materials: Carbon dioxide, Carbon monoxide and other asphyxiants. Section 11: TOXICOLOGICAL INFORMATION **EFFECTS OF ACUTE EXPOSURE Product Toxicity** Oral: Not available. Dermal: Not available. Inhalation: Not available. **Component Toxicity**

Section 10: STABILITY AND REACTIVITY

Component Distillates (petroleum), solvent-dewaxed light	CAS No. 64742-56-9	LD ₅o oral > 5000 mg/kg (rat)	LD₅₀ dermal > 2000 mg/kg (rabbit)	LC ₅₀ > 5.53 mg/L (rat); 4H
paraffinic Dodecyl alcohol, ethoxylated	9002-92-0	1000 mg/kg (rat)	> 2000 mg/kg (rabbit)	Not available.

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Target Organs:Skin. Eyes. Gastrointestinal tract. Respiratory system.

Symptoms (including delayed and immediate effects)

- **Inhalation:** Vapours and/or mists which may be formed at elevated temperatures may be irritating. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.
- **Eye:** Slightly irritating to the eyes. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Hot liquid product may cause serious thermal burns on direct contact.
- **Skin:** May cause skin irritation. May cause skin dryness and defatting of the skin. Signs/symptoms may include localized redness, swelling, and itching. Hot liquid product may cause serious thermal burns on direct contact.





SAFETY DATA SHEET

Date of Preparation: June 14, 2021

Ingestion: May be fatal if swallowed and enters airways. May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Skin Sensitization:	Not available.
Respiratory Sensitization:	Not available.
Medical Conditions Aggravated By Exposure:	Not available.

EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)

Target Organs:Skin. Eyes. Gastrointestinal tract. Respiratory system. Blood. Bone
marrow. Liver. Lymphoid tissue.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

 Carcinogenicity:
 The mineral oils in the product contain < 3% DMSO extract (IP 346).</td>

 Not considered to be carcinogenic. This product does not contain any carcinogens or potential carcinogens as listed by ACGIH, IARC, OSHA, or NTP.

 Mutageniaity:

Mutagenicity:	Not available.

Reproductive Effects: Not available.

Developmental Effects Teratogenicity: Not available.

Embryotoxicity: Not available.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION		
Ecotoxicity:	Distillates (petroleum), solvent-dewaxed light and heavy paraffinic: Acute EC50 >100 mg/L, Algae, 72 hours Acute EC50 >100 mg/L, Daphnia, 48 hours Acute EC50 >100 mg/L, Fish, 96 hours	
	Dodecan-1-ol, ethoxylated: Acute LC50 6460 μg/l, Fresh water, Daphnia magna, 48 hours Acute LC50 1500 μg/l, Fresh water, Salmo salar – Parr, 96 hours	
Persistence / Degradabili	ty: Considered to be inherently biodegradable.	
Bioaccumulation / Accumulation:	Constituents show measured or predicted values for log Kow from 2 to \geq 6 and are considered potentially bioaccumulative.	
Mobility in Environment:	Not available.	
Other Adverse Effects:	Not available.	
Section 13: DISPOSAL CONSIDERATIONS		
Disposal Instructions:	Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.	



Date of Preparation: June 14, 2021

Section 14: TRANSPORT INFORMATION

Canada Transportation of Dangerous Goods (TDG) Proper Shipping Name: Not regulated.		
Not applicable.		

Section 15: REGULATORY INFORMATION

Chemical Inventories

Canada (DSL)

This product contains a registered pesticide regulated under the Pest Control Products Act (PCPA). All other substances are in compliance with the Canadian Environmental Protection Act (CEPA, 1999).

Section 16: OTHER INFORMATION

Other information: PCP Registration No. 28124

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for their own particular use.

Date of Preparation of SDS:	June 14, 2021
Version:	1.1
GHS SDS Prepared by:	Aegis Regulatory Inc. Phone: (519) 488-0351
	www.aegisreg.com

Aegis Regulatory Inc.